

LIMITED EDITION STATE-OF-THE-ART SYSTEM
RECOMMENDED BY R. B. HASSING

CS100 COMPACT SPEAKERS AND INTEGRATED TUBE HYBRID AMPLIFIER



The CS100 compact speakers are the perfect answer for “space challenged” rooms. These speakers may be compact in size, but there is nothing compact about their sound. Using a 4-inch aluminum fiberglass matrix woofer and a 1-inch nano-silk dome tweeter, the CS100 provides crystal clear sound for music or home theater. These speakers have been paired with our integrated tube hybrid amplifier for an excellent small compact stereo system. An iPod or MP3 player can be plugged into the amplifier for hours of musical enjoyment. The low distortion characteristics of the speaker combined with the absence of odd order harmonic distortion in the tube amplifier produce a sweet, pure and extremely accurate sound.

Engineered Music Products

Layton, UT • USA • 801.991.1308 • www.emptek.com

EMP
Tek

TUBE AMPLIFIER



FRONT VIEW



BACK VIEW

MODEL NAME

VT-40.2

AMPLIFIER TYPE

Integrated Tube Hybrid

AC INPUT

110V±10%/60Hz

POWER OUTPUT

40 Watts Per Channel @ 8 Ohms
60 Watts Per Channel @ 4 Ohms

FREQUENCY RESPONSE

20Hz — 20kHz

DISTORTION (THD)

< 2%

S/N RATIO

> 80dB

PASS BAND

10Hz — 100kHz

SIGNAL INPUT (ANALOG)

- AUX (1/8-inch jack)
- iPod/MP3 (1/8-inch jack)
- R/L (CD/DVD) (RCA jacks)

LINE LEVEL INPUT SENSITIVITY

450mV

DIMENSIONS

6-5/8" W x 4-1/2" H x 10-1/4" D
(168mm W x 114mm H x 260mm D)

WEIGHT

8 Lbs. (3.63 Kg)

WARRANTY

1 Year

CS100 BOOKSHELF SPEAKER

MODEL NAME

CS100

SYSTEM TYPE

Bookshelf Speaker

FREQUENCY RESPONSE

60Hz — 20kHz ± 3dB

SENSITIVITY

85dB (2.83 Volts @ 1 Meter)

RECOMMENDED POWER

15-100 Watts

DRIVE UNITS

(1) 4" (102mm) Aluminized Fiberglass

Matrix (AFM) Woofer

(1) 1" (25mm) Nano-silk Dome Tweeter

CROSSOVER FREQUENCY

3,000 Hz

CROSSOVER

12dB/Octave

IMPEDANCE

8 Ohms

CABINET

Black

GRILLE

Black

DIMENSIONS

5" W x 7-3/4" H x 5"

(127mm W x 196mm D)

WEIGHT

3 Lbs. (1.36 Kg)

WARRANTY

5 Years



EMP

Tek

Engineered Music Products

801.991.1308 • www.emptek.com

All specifications are subject to change without notice.
Copyright © 2009 EMP Tek. All Rights Reserved.